NEMO

RAKE



RAKE




RAKE

RAKE

WHITE

GROOVE WHITE

BISQUE

GROOVE BISQUE

SHELL



GROOVE SHELL

MOON



GROOVE MOON

MIST

GROOVE MIST

LAGRIMA WHITE


*LAGRIMA AVAILABLE IN WHITE ONLY

*RAKE IS AN EXTRUDED PORCELAIN TILE, IT IS NOT A PRESSED TILE. EXTRUDED TILES HAVE VARIATIONS IN SIZE BETWEEN TILES AND MAY APPEAR INCONSISTENT. WE RECOMMEND USING A GROUT JOINT OF 3-4MM. WE RECOMMEND USING A GROUT COLOR THAT WILL COMPLEMENT THE PRODUCT, AS CONTRASTING GROUT COLORS MAY ACCENTUATE THE VARIATION IN PRODUCT SIZE.


RAKE




GROOVE BERBER



GROOVE TURQUOISE



GROOVE CHARTREUSE



GROOVE COBALT



GROOVE ROUGE



GROOVE TOBACCO



GROOVE SPICE


3” x 8.5” (7.2 x 22.2 cm) EXTRUDED PORCELAIN TILE




3″ x 8.5″



3″ x 4″
LAGRIMA



3″ x 8.5″



1″ x 8.5″
DEMI BULLNOSE

RAKE



RAKE

PACKAGING

Size	Thickness	Pieces / Box	Sq. Ft. / Box	Box / Pallet	Lbs/ Carton
3.5”x8.5” / 7.2x22.2 cm	3/8”	50	8.61	60	39
Lagrima 4”x3” / 11x8 cm	13/32”	45	4.3	132	16

TECHNICAL FEATURES

Type	Test Method	Requirements
Reference Rule	ISO - 14411 Annex 13	
Membership Group	Group A1	
Water Absorption	UNE-EN-ISO 10545-3	0.2%
Frost Resistance	UNE-EN-ISO 10545	within specifications
Chemical Resistance	UNE-EN-ISO-10545	Resistant
Skid Resistance	DIN 51097	Group A
Skid Resistance	UNE-ENV 12633:2003	Class 1: Friction < 0.4 satisfactory for normal installations Class 2: Friction > 0.4 recommended for installations where is required high skid resistance
Bending Resistance	UNE-EN-ISO-10545-4	31 N/mm^2
Cracking Resistance	UNE-EN-ISO-10545-11	within specifications

NEMO



NEMO

NEMOTILE.COM

RAKE