NEMO

VOLCANO



VOLCANO



VOLCANO



VOLCANO PORCELAIN TILE

COLORS

BIANCO



CENERE



GRIGIO



SABBIA



TORTORA



NERO

MOSAICS



2x2 MOSAIC
ON 12X12 SHEET

AVAILABLE IN GRIGIO, BIANCO, AND SABBIA

VOLCANO

SIZES




12x24



6x36



6x12



2x2 mosaic on
12x12 sheet

VOLCANO



VOLCANO

PORCELAINED STONEWARE WITH MASS COLORING
Bla GL
Class 2 ISO 13006

TECHNICAL FEATURES	UNIT OF MEASUREMENT	MEAN VALUE	FIXED VALUE	TEST METHOD
DIMENSIONS LENGTH & WIDTH	%	+/- 0.4	+/- 0.6 MAX	UNI EN ISO 10545-2
SIDE STRAIGHTNESS	%	+/- 0.4	+/- 0.5 MAX	UNI EN ISO 10545-2
CORNER SQUARENESS	%	+/- 0.4	+/- 0.6 MAX	UNI EN ISO 10545-2
FLATNESS	%	+/- 0.4	+/- 0.5 MAX	UNI EN ISO 10545-2
THICKNESS	%	+/- 5.0	+/- 5.0 MAX	UNI EN ISO 10545-2
WATER ABSORPTION	%	< 0.2	≤ 0.5	UNI EN ISO 10545-3
BREAKING STRENGTH	N	> 1600	≥ 1300 SE SPESS. ≥ 7.5 ≥ 700 SE SPESS ≤ 7.5	UNI EN ISO 10545-4
MODULUS OF RUPTURE	N/mm^2	> 40	≥ 35	UNI EN ISO 10545-4
COEFFICIENT OF LINEAR THERMAL EXPANSION	° MK (-1)	7.0	AVAILABLE METHOD	UNI EN ISO 10545-8
THERMAL SHOCK RESISTANCE	-	RESISTANT	AVAILABLE METHOD	UNI EN ISO 10545-9
STAIN RESISTANCE	-	≥ 3	3 MIN.	UNI EN ISO 10545-14
RESISTANCE TO CHEMICAL PRODUCTS	-	CONFORM	MIN GB	UNI EN ISO 10535-13
RESISTANT TO ACID AND LOW CONCENTRATION BASES	-	GLA	AVAILABLE METHOD	UNI EN ISO 10545-13
FROST RESISTANCE	-	RESISTANT	REQUEST	UNI EN ISO 10545-12
COLOR STABILITY	-	STABLE	AVAILABLE METHOD	DIN 51094

NEMO



NEMO

NEMOTILE.COM

VOLCANO