

 **NEMO**

**CROSS COLORS
MINGLES**



CROSS COLORS MINGLES



CROSS COLORS MINGLES



CROSS COLORS

MINGLES

PORCELAIN
COLORS



A235
SAHARA DUNE II



A238
SHETLAND II



A239
PEPPER QUARTZ II



A260
PEBBLE II




A246
PACIFIC SURF II



A236
FLAX



A750
BROWN TWEED



A233
SAND BISQUE




A658
FAWN



A825
MERCURY*



A375
SAFFRON




A740
NUTMEG



A876
TRUFFLE*




A485
RAINFOREST




A830
ATLANTIC GREY




A745
TAWNY




A675
STONEHENGE* AC




A410
GREENBRIAR II




A900
MICA* AC



A585
SEA MIST* II




A760
SPICE MIST* I




A660
ROSEWOOD I




A790
BURGUNDY SMOKE* AC




A850
GRAPHITE* AC



A880
ONYX* II



EC001
STORM**




R001
GREY MINGLE**

CROSS COLORS


PORCELAIN

LP


COLORS




LA21
ROCK CRYSTAL




LA26
WHITE CORAL




LA87
CAPPUCCINO




LA90
GRANITE GREY




LA45
JADESTONE



LA58
BLUE SPLASH



LA48
SNOWPINE



LA63
RED ROCK



LA88
BLACK PEARL

TEXTURES & FINISHES

Cross-Slate (CS) - The cross-slate finish combines the rustic and textured feel of slate with the through-body color and durability of Porcelain Stone. Through-body colour, unglazed structured surface, and a variety of sizes provide a strong commercial value where enhanced traction is needed for high traffic interior and exterior spaces. Cross-Slate is recommended for interior floors and walls as well as exterior walls and exterior walking surfaces in both residential and commercial environments.


Cross-Tread (CTS) - Increased slip resistance and ease of maintenance make this tile a suitable choice for wet and greasy floor areas, as well as for exterior walking surfaces. The Cross-Tread surface pattern is eye-catching, making it a great option for transitional areas and for use as an accent tile.

Crossdot (CD) - The raised-dot pattern, with a “roughened” surface atop each dot, provides increased coefficient of friction. It is suitable for most commercial kitchens, food prep areas, service stations and other back-of-the-house areas, as well as for exterior walking surfaces.


Cross-Grip (CGS) - Developed in conjunction with restaurant owners, Cross-Grip is a possible solution for those areas where slips and falls are of greatest concern. The patented raised-point texture has earned Cross-Grip the highest possible performance rating in the National Restaurant Association’s testing for slip resistance. It is suitable for areas where grease, food, oil and other residue tend to accumulate.



Unpolished (UPS)



Polished (PO)




Cross-Slate (CS)



Cross-Tread (CTS)



Crossdot (CD)




Cross-Grip (CGS)


FINISHES INFORMATION

Cross Colors A Series	6x6 (cut/bevel)	8x8	12x12
A233 Sand Bisque*	● ● ● ● ● ●	● ●	● ●
A235 Sahara Dune*	● ● ●	● ● ● ●	● ● ●
A236 Flax	● ●	● ●	● ●
A238 Shetland	● ●	● ●	● ●
A246 Pacific Surf	● ●	● ●	● ●
A260 Pebble*	● ●	● ● ●	● ●
A291 Pepper Quartz*	● ●	● ●	● ●
A375 Saffron	● ●	● ●	● ●
A410 Greenbriar	● ●	● ● ●	● ●
A485 Rain Forest	● ●	● ●	● ●
A585 Sea Mist	● ● ●	● ● ● ●	● ● ●
A658 Fawn	● ●	● ●	● ●
A660 Rosewood	● ●	● ● ●	● ●
A675 Stonehenge*	● ● ●	● ● ● ● ● ● ●	● ● ●
A740 Nutmeg	● ●	● ●	● ●
A745 Tawny	● ● ●	● ● ●	● ● ●
A750 Brown Tweed*	● ● ●	● ● ● ●	● ● ●
A760 Spice Mist*	● ●	● ●	● ●
A790 Burgundy Smoke*	● ●	● ● ● ● ● ●	● ●
A825 Mercury*	● ● ●	● ● ● ●	● ● ●
A830 Atlantic Grey	● ●	● ●	● ●
A850 Graphite*	● ● ●	● ● ● ● ● ●	● ● ●
A876 Truffle	● ● ●	● ● ●	● ● ●
A880 Onyx*	● ● ●	● ● ● ●	● ● ●
A900 Mica*	● ● ●	● ● ● ● ● ● ●	● ● ●
EC001 Storm		● ●	
R001 Grey Mingle		● ●	

- Unpolished (UPS) ● Polished (PO)
- Cross-Slate (CS) ● Cross-Tread (CTS)
- Crossdot (CD) ● Cross-Grip (CGS)



12x12



8x8



6x6

FIELD TILE SIZES & FINISHES

Nominal (in)	Actual (in)	Thickness (in)	Finish
6 x 6 (cut/bevel)	5 $\frac{3}{4}$ x 5 $\frac{3}{4}$	$\frac{5}{16}$	UPS/PO
8 x 8 (A & C colors only)	7 $\frac{3}{4}$ x 7 $\frac{3}{4}$	$\frac{5}{16}$	UPS/PO
12 x 12	11 $\frac{3}{4}$ x 11 $\frac{3}{4}$	$\frac{5}{16}$	UPS/PO



Cove Base
(Standard, round top)



Inside & Outside
Cove Base Corner



Cove Base Corner -
Left




Cove Base Corner -
Right



Bullnose



Left & Right
Bullnose Corners



Bullnose Stair
Tread



Mounted Bullnose
1 Linear Foot



Bullnose
Corner



Mounted Cove Base
1 Linear Foot

V1

Uniform Appearance.

TECHNICAL INFORMATION

Specification	Test	Cross Colors Mingles
Breaking Strength	ASTM C648	350-420 lbf
Bond Strength	ASTM C482	> 200 psi
Chemical Resistance	ASTM C650	Unaffected
Frost Resistance	ASTM C1026	Resistant
Water Absorption	ASTM C373	< 0.10%
Scratch Hardness	MOHS Scale	UPS, CS, CTS, CD, CGS: 6 PO: 5
DCOF	AcuTest	Unpolished (UPS): 0.50 - 0.60 Cross-Slate (CS): 0.50 - 0.60 Cross - Treat (CTS)*: 0.50 - 0.60 Crossdot (CD)*: 0.50 - 0.60 Cross - Grip (CGS)**: - Polished (PO): 0.31 - 0.41

*The increased real world traction of these types of surfaces cannot be fully realized by any current COF testing methodologies due to their exaggerated structures

**Due to the heavily texture surface DCOF value is not able to be measured by testing device



 **NEMO**
NEMOTILE.COM
CROSS COLORS
MINGLES