NEMO

CASABLANCA



CASABLANCA




CASABLANCA

CASABLANCA HEXAGON
COLORS

PORCELAIN WALL & FLOOR



CLOUD



SAHARA



SMOKE










MIST





PALM



RIVER







CASABLANCA HEXAGON



WIND



NIGHT








V3 Variation: The product has deliberately moderate variation in the shading, resulting from the original grain or veining of the natural materials, or produced to suggest vintage effects, an aged look or a particular texture.

*Single tile image is representative of one color swatch from a variant group
**Matte Finish
*** Hand finished / distressed edge look



*Enlarged image shown to represent hand finished / distressed look of the edge condition of tile

CASABLANCA SQUARE
COLORS

WHITE BODY WALL TILE



CLOUD




SAHARA



SMOKE









MIST




PALM



RIVER








CASABLANCA SQUARE



WIND



NIGHT







V3 Variation: The product has deliberately moderate variation in the shading, resulting from the original grain or veining of the natural materials, or produced to suggest vintage effects, an aged look or a particular texture.

*Single tile image is representative of one color swatch from a variant group
**Gloss Finish
*** Hand finished / distressed edge look




*Enlarged image shown to represent hand finished / distressed look of the edge condition of tile

CASABLANCA MIX


PORCELAIN WALL & FLOOR




NIGHT MIX



PALM MIX



RIVER MIX



SAHARA MIX



WHITE BODY WALL TILE


CASABLANCA MIX



NIGHT MIX



PALM MIX




RIVER MIX




SAHARA MIX



CASABLANCA



5.5″ x 6.3″



5″ x 5″

FIELD TILE SIZES & FINISHES

Nominal (in)	Actual (cm)	Thickness (in)	Finish
5.5” x 6.3” Hexagon	$^{13}.^{9}$ x $^{16}.^{3}$	3/8	Matte
5” x 5” Square	13 x 13	3/8	Glazed

CASABLANCA HEXAGON / PORCELAIN TILES / GROUP: BIa

TECHNICAL FEATURE	EUROPEAN NORM	VALUE
SIZE, THICKNESS, SIDE STRAIGHTNESS, FLATNESS, ORTHOGONALITY	UNE - EN - 14411	ACCOMPLISHES ALL REQUIREMENTS
WATER ABSORPTION CAPACITY	EN ISO 10545 - 03	> 10%
FLEXION RESISTANCE	EN ISO 10545 - 04	> 15 N/mm²
RESISTANCE TO THE ABRASION, METHOD PEI	EN ISO 10545 - 07	IV
THERMAL SHOCK RESISTANCE	EN ISO 10545 - 09	CONFORMS
CRACKING RESISTANCE	EN ISO 10545 -11	CONFORMS
FROST RESISTANCE	EN ISO 10545 - 12	CONFORMS
RESISTANCE TO ACIDS (LOW AND HIGH CONCENTRATIONS)	EN ISO 10545 - 13	GLA / GHA
RESISTANCE TO ALKALIS	EN ISO 10545 - 13	GLA / GHA
RESISTANCE TO CLEANING PRODUCTS	EN ISO 10545 - 13	GA
RESISTANCE TO CHEMICAL PRODUCTS TO SWIMMING POOL WATER	EN ISO 10545 - 13	GA
STAINS RESISTANCE	EN ISO 10545 - 14	5
SLIP RESISTANCE (RD)	ENV12633	CLASS 3
SLIP RESISTANCE (S)	DIN 51130	R10
SLIP RESISTANCE (DCOF)	ANSI A137.1	> 0.60

CASABLANCA SQUARE /WHITE BODY WALL TILES / GROUP: BIII

TECHNICAL FEATURE	EUROPEAN NORM	VALUE
SIZE, THICKNESS, SIDE STRAIGHTNESS, FLATNESS, ORTHOGONALITY	UNE - EN - 14411	ACCOMPLISHES ALL REQUIREMENTS
WATER ABSORPTION CAPACITY	EN ISO 10545 - 03	> 10%
FLEXION RESISTANCE	EN ISO 10545 - 04	> 15 N/mm²
LINEAR THERMAL EXPANSION	EN ISO 10545 - 08	< 7*10-6°-1
THERMAL SHOCK RESISTANCE	EN ISO 10545 - 09	CONFORMS
CRAZING RESISTANCE	EN ISO 10545 - 11	CONFORMS
RESISTANCE TO ACIDS (HIGH AND LOW CONCENTRATIONS)	EN ISO 10545 - 13	GHA & GLA
RESISTANCE TO ALKALIS	EN ISO 10545 - 13	GHA & GLA
RESISTANCE TO CLEANING PRODUCTS	EN ISO 10545 - 13	GA
RESISTANCE TO CHEMICAL PRODCUTS AND SWIMMING POOLS	EN ISO 10543 - 13	GA
STAINS RESISTANCE	EN ISO 10545 - 14	5



V3 Variation: The product has deliberately moderate variation in the shading, resulting from the original grain or veining of the natural materials, or produced to suggest vintage effects, an aged look or a particular texture.



NEMO

NEMOTILE.COM

CASABLANCA