

# NEMO

## LIFE



**LIFE**





**LIFE**



# LIFE

## COLORS



NORDIC



OAK



NOCE




WALNUT

## SIZES



8" x 48"

\* Available in Natural and Textured Finishes



**V2**

Slight Variation





## TECHNICAL FEATURES

|                                 | STANDARD     | ESTABLISHED LIMITS                                                                         | MEASURED VALUES                              |
|---------------------------------|--------------|--------------------------------------------------------------------------------------------|----------------------------------------------|
| <b>SIZE</b>                     | ISO 10545.2  | In accordance                                                                              | In accordance                                |
| <b>THICKNESS</b>                |              | 9 mm                                                                                       | 20 mm                                        |
| <b>WATER ABSORPTION</b>         | ISO 10545.3  | 0.05%                                                                                      | ≤ 0.1%                                       |
| <b>THERMAL SHOCK</b>            | ISO 10545.9  | Resistant                                                                                  | Resistant                                    |
| <b>CHEMICAL RESISTANCE</b>      | ISO 10545.13 | Resistant                                                                                  | Resistant                                    |
| <b>STAINS<br/>RESISTANCE</b>    | ISO 10545.14 | Cleanable                                                                                  | Cleanable                                    |
| <b>ANTI SLIP<br/>VALUE</b>      | D-COF        | Natural Wet: ≥ 0.60<br>Natural Dry: ≥ 0.60<br>Textured Wet: ≥ 0.70<br>Textured Dry: ≥ 0.70 | Textured Wet: ≥ 0.70<br>Textured Dry: ≥ 0.70 |
| <b>FROST RESISTANT</b>          | ISO 10545.12 | Resistant                                                                                  | Resistant                                    |
| <b>BREAKING STRENGTH</b>        | ISO 10545.4  | Spa ≥ 7.5 mm<br>≤ 1300 N                                                                   | >10,000                                      |
| <b>BENDING STRENGTH</b>         | ISO 10545.4  | In accordance                                                                              | N/A                                          |
| <b>DEEP SCRATCH RESISTANCE</b>  | ISO 10545.8  | ≤ 145 mm³                                                                                  | ≤ 145 mm³                                    |
| <b>THERMAL LINEAR EXPANSION</b> | ISO 10545.8  | ≈ 6.5 (10 <sup>-6</sup> C <sup>-1</sup> )                                                  |                                              |
| <b>EXPANSION IN HUMIDITY</b>    | ISO 10545.10 | ≤ 0.1 (mm/m)                                                                               | ≤ 0.1 (mm/m)                                 |



 **NEMO**  
NEMOTILE.COM  
**LIFE**